

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

1 Identification of substance

· Product details

· Trade name: 43645 (Hardman Epocap 3645 Part A)

· Article number: 43645

· Manufacturer/Supplier:

Royal Adhesives And Sealants, LLC

2001 W. Washington Street South Bend IN 46628-2023

· Information department: Environment protection department.

· Emergency information: ChemTrec: UNITED STATES 1(800)424-9300 INTERNATIONAL 202-483-7616

2 Composition/Data on components

- · Chemical characterization
- · **Description:** Mixture of the substances listed below with nonhazardous and Trade Secret addition(s).
- · Dangerous components:

For Trade Secret information refer to 29 CFR 1910.120.

| | -r · · · · · · · · · · · · · · · · · · · | 50-100% |
|---|--|---------|
| ı | Warning: 🕦 3.2/2, 3.3/2A, 3.4.S/1 | |
| | ♦ 4.1.C/2 | |
| Ī | butyl glycidyl ether | 10-25% |
| | Warning: 🚸 2.6/3; 🕸 3.5/2, 3.6/2; 🕦 3.1.0/4, 3.1.I/4, 3.4.S/1, 3.8/3 | |
| | 4.1.C/3 | |

· Additional information: For the wording of the listed risk phrases refer to section 15.

3 Hazards identification

· Hazard description:

Harmful

Dangerous for the environment

· Information pertaining to particular dangers for man and environment:

Irritating to eyes and skin.

Limited evidence of a carcinogenic effect.

May cause sensitisation by skin contact.

Possible risk of irreversible effects.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

Contains epoxy constituents. See information supplied by the manufacturer.

· Classification system:

The classification was made according to the latest editions of international substances lists, and expanded upon from company and literature data.

· NFPA ratings (scale 0 - 4)



Health = 3 Fire = 2Reactivity = 0

(Contd. on page 2)

(Contd. of page 1)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

Trade name: 43645 (Hardman Epocap 3645 Part A)

· HMIS-ratings (scale 0 - 4)

HEALTH3Health = 3FIRE2Fire = 2PHYSICAL HAZARD $\boxed{0}$ $Physical\ Hazard = 0$

· GHS label elements

Health hazard Warning

3.5/2 - Suspected of causing genetic defects.

3.6/2 - Suspected of causing cancer.

Exclamation mark Warning

3.2/2 - Causes skin irritation.

3.3/2A - Causes serious eye irritation.

3.4/1 - May cause an allergic skin reaction.

Warning

2.6/4 - Combustible liquid.

Environment

4.1/2 - Toxic to aquatic life with long lasting effects.

· Prevention:

Keep away from heat/sparks/open flames/hot surfaces. - No smoking.

Avoid breathing dust/fume/gas/mist/vapours/spray.

· Response:

IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.

Specific treatment (see on this label).

· Storage:

Store locked up.

· Disposal:

Dispose of contents/container in accordance with local/regional/national/international regulations.

4 First aid measures

· After inhalation:

Remove to fresh air. If not breathing, administer artificial respiration. If breathing is difficult, oxygen should be administered by qualified personnel. Call a physician or transport to a medical facility.

- · After skin contact: Immediately wash with water and soap and rinse thoroughly.
- · After eye contact:

Rinse opened eye for 15 minutes under running water. If eye becomes irritated, obtain medical treatment.

· After swallowing:

Drink two glasses of water and immediately induce vomiting. Never give fluids if victim is ouconscious or having convulsions. Seek immediate medical attention.

Immediately call a doctor.

Seek medical treatment.

5 Fire fighting measures

· Suitable extinguishing agents:

CO2, extinguishing powder or water spray. Fight larger fires with water spray.

Use fire fighting measures that suit the environment.

· Protective equipment: Protective clothing and respiratory protective device.

USA ·

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

Trade name: 43645 (Hardman Epocap 3645 Part A)

(Contd. of page 2)

6 Accidental release measures

- · Person-related safety precautions: Wear protective equipment. Keep unprotected persons away.
- Measures for environmental protection: Do not allow to enter sewers/ surface or ground water.
- · Measures for cleaning/collecting:

Absorb with liquid-binding material (sand, diatomite, acid binders, universal binders, sawdust). Dispose of contaminated material as waste in accordance with federal state and local regulations. Ensure adequate ventilation.

7 Handling and storage

- · Handling:
- · Information for safe handling: Ensure good ventilation/exhaustion at the workplace.
- · Information about protection against explosions and fires: No special measures required.
- · Storage:
- · Requirements to be met by storerooms and receptacles: Store in a cool location away from direct heat.
- · Information about storage in one common storage facility: Keep away from open flames and high temperatures.
- · Further information about storage conditions: Store in cool, dry conditions in well sealed receptacles.

8 Exposure controls and personal protection

- · Additional information about design of technical systems: No further data.
- · Components with limit values that require monitoring at the workplace:

2426-08-6 butyl glycidyl ether (10-25%)

PEL 270 mg/m³, 50 ppm

REL Short-term value: C 30* mg/m³, C 5.6* ppm

*15-min

TLV 16 mg/m³, 3 ppm

Skin; SEN

- · Additional information: The lists that were valid during the creation were used as basis.
- · Personal protective equipment (see listings below)
- · General protective and hygienic measures:

Keep away from foodstuffs, beverages and feed.

Immediately remove all soiled and contaminated clothing.

Wash hands before breaks and at the end of work.

Avoid contact with the eyes and skin.

· Breathing equipment:

Use approved respiratory protection equipment when airborne exposure is excessive. Consult the respirator manufacturer to determine the appropriate type of equipment for a given application. Observe respirator use limitations specified by the manufacturer.

· Protection of hands:

Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation.

· Material of gloves

Nitrile rubber, NBR

Chloroprene rubber, CR

(Contd. on page 4)

- USA

(Contd. of page 3)

Material Safety Data Sheet acc. to ISO/DIS 11014

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

Trade name: 43645 (Hardman Epocap 3645 Part A)

· Eye protection:

Safety glasses with side shields.



Tightly sealed goggles

· Body protection:

Emergency showers and eye wash stations should be available.

Protective work clothing

| 9 Physical | and | chemical | properties |
|------------|-----|----------|------------|
| | | | |
| | | | |

| · General Information | | | | | |
|--|---|--|--|--|--|
| Form: | Liquid | | | | |
| Color: | Clear | | | | |
| Odor: | Characteristic | | | | |
| · Change in condition | | | | | |
| Melting point: | Undetermined. | | | | |
| Boiling point: | Undetermined. | | | | |
| · Flash point: | 73°C (163°F) | | | | |
| · Ignition temperature: | 215°C (419°F) | | | | |
| · Auto igniting: | Product is not selfigniting. | | | | |
| · Danger of explosion: | Product does not present an explosion hazard. | | | | |
| · Vapor pressure at 20°C (68°F): 3.5 hPa (3 mm Hg) | | | | | |
| · Specific gravity at 20°C (68°F): 1.14 g/cm³ | | | | | |
| · Solubility in / Miscibility with | | | | | |
| Water: | Not miscible or difficult to mix. | | | | |
| · Solvent content: | | | | | |
| Organic solvents: | 0.0 % | | | | |
| VOC (Per EPA 24) | N/A GMS/L | | | | |
| Solids content: | 86.4 % | | | | |

10 Stability and reactivity

- · Thermal decomposition / conditions to be avoided: No decomposition if used according to specifications.
- · Materials to be avoided:
- · Dangerous reactions Strong oxidizing agents.
- · Dangerous products of decomposition: Carbon Monoxide, Carbon Dioxide, Aldehydes, acids.

USA

(Contd. on page 5)

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

Trade name: 43645 (Hardman Epocap 3645 Part A)

(Contd. of page 4)

11 Toxicological information

· Acute toxicity:

· LD/LC50 values that are relevant for classification:

2426-08-6 butyl glycidyl ether

Oral LD50 2050 mg/kg (rat)
Dermal LD50 2520 mg/kg (rabbit)

- · Primary irritant effect:
- · on the skin:

May be severely irritating to the skin.

May be toxic if absorbed.

· on the eye:

May be severely irritating to the eyes.

Vapors may be irritating to the eyes.

- · Sensitization: Skin Contact Sensitization possible through skin contact.
- · Additional toxicological information:

May be slightly toxic and may be harmful if swallowed.

Preexisting eye, skin and respiratory disorders may be aggravated by exposure to this product.

12 Ecological information

- · Ecotoxical effects:
- · Remark: Toxic for fish
- · Additional ecological information:
- · General notes:

Water hazard class 2 (Self-assessment): hazardous for water

Do not allow product to reach ground water, water course or sewage system.

Also poisonous for fish and plankton in water bodies.

Toxic for aquatic organisms

13 Disposal considerations

- · Product:
- · Recommendation:

Disposal must be made according Federal, State and local regulations.

Must not be disposed of together with household garbage. Do not allow product to reach sewage system.

- · Uncleaned packagings:
- · Recommendation:

Disposal must be made according to official regulations.

Packagings that cannot be cleansed are to be disposed of in the same manner as the product.

14 Transport information

· DOT regulations: Non-hazardous via all transport modes.

· Hazard class:

Non-Hazardous

(Contd. on page 6)

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

Trade name: 43645 (Hardman Epocap 3645 Part A)

(Contd. of page 5)

- · Land transport ADR/RID (cross-border):
- · ADR/RID class:

Not Regulated

- · Maritime transport IMDG:
- · IMDG Class:

Not Regulated

- · Air transport ICAO-TI and IATA-DGR:
- · ICAO/IATA Class: -

Not Regulated

- · UN "Model Regulation": -
- · Transport/Additional information:

The above information applies to non-bulk containers.

Not regulated by D.O.T. if in a container of 119 gallon capacity or less.

Epoxy Resin - This product is not considered to be DOT hazardous when transported via any mode within the United States. However, if this product is transported to or within the European Community it is considered to be an Environmentally Hazardous Substance, Liquid Epoxy Resin, UN3082, Class 9.

15 Regulations

- · Sara
- · Section 355 (extremely hazardous substances):

None of the ingredients is listed.

· Section 313 (Specific toxic chemical listings):

None of the ingredients is listed.

· TSCA (Toxic Substances Control Act):

All components of this product are on the TSCA Inventory or are exempt from TSCA Inventory requirements.

- · Proposition 65
- · Chemicals known to cause cancer:

None of the ingredients is listed.

· Chemicals known to cause reproductive toxicity:

None of the ingredients is listed.

· (DSL) Canada Dosmestic Substance List

All components of this product are on the DSL(Canada Domestic Substance list) or are exempt from DSL requirements.

- · Cancerogenity categories
- · EPA (Environmental Protection Agency)

None of the ingredients is listed.

· IARC (International Agency for Research on Cancer)

None of the ingredients listed.

· NTP (National Toxicology Program)

None of the ingredients is listed.

· TLV (Threshold Limit Value established by ACGIH)

None of the ingredients listed.

(Contd. on page 7)

Printing Date 07/12/2010 Revision Number 2 Reviewed on 10/08/2009

Trade name: 43645 (Hardman Epocap 3645 Part A)

(Contd. of page 6)

· MAK (German Maximum Workplace Concentration)

2426-08-6 butyl glycidyl ether

3B

· NIOSH-Ca (National Institute for Occupational Safety and Health)

None of the ingredients is listed.

· OSHA-Ca (Occupational Safety & Health Administration)

None of the ingredients is listed.

· Product related hazard informations:

The product has been classified and marked in accordance with directives on hazardous materials.

· Hazard-determining components of labelling:

Epoxy Resin

butyl glycidyl ether

· Risk phrases:

Irritating to eyes and skin.

Limited evidence of a carcinogenic effect.

May cause sensitisation by skin contact.

Possible risk of irreversible effects.

Toxic to aquatic organisms, may cause long-term adverse effects in the aquatic environment.

· Special labeling of certain preparations:

Contains epoxy constituents. See information supplied by the manufacturer.

- · National regulations:
- · Water hazard class: Water hazard class 2 (Self-assessment): hazardous for water.

16 Other information

Although the information and recommendations set forth in this MSDS are presented in good faith and are believed to be correct as of the date of this MSDS, Royal Adhesives & Sealants makes no representations as to the completeness or accuracy thereof. Information is supplied on the condition that the persons receiving and using it will make their own determination as to the suitability for their purpose prior to use. In no event will Royal Adhesives & Sealants or any affiliate thereof be responsible for damages of any nature whatsoever resulting from the use or reliance on the information set forth in the MSDS.

· Department issuing MSDS: Environment protection department.

· Abbreviations and acronyms:

ADR: Accord européen sur le transport des marchandises dangereuses par Route (European Agreement concerning the International Carriage of Dangerous Goods by Road)

RID: Reglement international concernant le transport des marchandises dangereuses par chemin de fer (Regulations Concerning the International Transport of Dangerous Goods by Rail)

IMDG: International Maritime Code for Dangerous Goods

DOT: US Department of Transportation

IATA: International Air Transport Association

IATA-DGR: Dangerous Goods Regulations by the "International Air Transport Association" (IATA)

ICAO: International Civil Aviation Organization

ICAO-TI: Technical Instructions by the "International Civil Aviation Organization" (ICAO)

GHS: Globally Harmonized System of Classification and Labelling of Chemicals

ACGIH: American Conference of Governmental Industrial Hygienists

NFPA: National Fire Protection Association (USA)

 ${\it HMIS: Hazardous\ Materials\ Identification\ System\ (USA)}$

LC50: Lethal concentration, 50 percent

LD50: Lethal dose, 50 percent

USA